



ARMA[®]

RIGID CONDUIT SYSTEMS

QUICK REFERENCE GUIDE



HOW TO SELECT PERFORMANCE BASED CONDUIT

As a craftsman, achieving best practice performance and compliance for all your electrical cable management work is important. When adhering to AS/NZS 3000:2018 Wiring Regulations, use this 3 point guide for selecting electrical conduit.

Not all conduit brands perform the same

KEY SELECTION FACTORS

- › Durability
- › Craftmanship
- › Assurance

BEST PRACTICE CONDUIT FEATURES

MARLEY ARMA[®]

1 DURABILITY

UV Protection



- Long term outdoor durability

Mechanical Protection



- Category A underground wiring rules compliance



- Heavy duty durability (compression and impact protection) at very low temperatures

Service Temperature



- At very low service temperatures (-15°C) does not become brittle (mid range performing conduit typically restricted to +5°C)



HD4431

-15°C to 60

2 CRAFTMANSHIP

Material Finish



- *High gloss finish* has superior resistance to scratching and soiling compared to *matte finish*

Fittings



- Colour match to Marley ARMA[®] conduit for a professional finish



- Extensive range for ease of install

Quality of cut



- Product retains shape once cut, unlike thinner wall product which may deform permanently

Gloss finish



3 ASSURANCE

- AS/NZS 61386



- 3rd Party independent verification

- Print markings for authenticity of performance



MARLEY ARMA[®] QUICK REFERENCE GUIDE

Marley ARMA's fully featured solutions make ABOVE GROUND and BELOW GROUND selection quick and easy.

ARMA[®] ABOVE GROUND

Product Code	Size	Pack
01.20HD.GY	20mm	80m (20 x 4m)
01.25HD.GY	25mm	40m (10 x 4m)
01.32HD.GY	32mm	40m (10 x 4m)
01.40HD.GY	40mm	24m (6 x 4m)
01.50HD.GY	50mm	24m (6 x 4m)


ARMA[®] BELOW GROUND

Product Code	Size	Pack
01.20HD.OR	20mm	80m (20 x 4m)
01.25HD.OR	25mm	40m (10 x 4m)
01.32HD.OR	32mm	40m (10 x 4m)
01.40HD.OR	40mm	24m (6 x 4m)
01.50HD.OR	50mm	24m (6 x 4m)

PRODUCT FEATURES



Feature	Above Ground	Below Ground
UV PROTECTION (T)	✓	✓
CATA UNDERGROUND (A)	✓	✓
HEAVY DUTY (HD)	✓	✓
SERVICE TEMPERATURE RANGE	✓	✓
HIGH GLOSS FINISH	✓	✓
COLOUR MATCH	✓	✓
EXTENSIVE FITTING RANGE	✓	✓
QUALITY OF CUT	✓	✓
COMPLIANCE	✓	✓



PRODUCT AUTHENTICITY

Not all brands of rigid conduit in the market perform to the same level. For proof of intended performance, check the mandatory print requirements that are marked on the conduit.

- 1 Manufacturer and/or brand name identification
- 2 Designed specifically to protect electrical wiring
- 3 Classification Rating
- 4 Compression Duty Rating (Rating 4 = Heavy Duty)
- 5 Impact Duty Rating (Rating 4 = Heavy Duty)
- 6 Minimum Service Temperature rating (Rating 3 = -15°C)
- 7 Maximum Service Temperature rating (Rating 1 = 60°C)
- 8 T= UV Protection Long Term
- 9 New Manufacturing Standard
- 10 3rd party License Verification for the specific manufacturing site
- 11 Exact date and time of manufacture and Marley item code for easy tracking

**IF IT'S NOT 4431
ASK WHY NOT?**

ABOVE GROUND
BELOW GROUND

MARLEY